

CHEMICAL INJECTION TANK

UNIT: CIT74

PERFORMANCE

| | |
|----------------------------|------------------------------|
| Maximum Discharge Pressure | 3000 psi (20684 kPa) |
| Liquid Storage Capacity | 100 Gallon (378.5 Liters) |
| Secondary Containment | Sealed Secondary Containment |

DRIVE

| | |
|------------|-----------------|
| Model | Baldor Reliance |
| Horsepower | .25 HP |
| RPM | 1725 |
| Volts | 115/208-230 |
| Amps | 4.2/2-2.1 |
| Hertz | 60 |

PUMP

| | |
|-----------|-----------|
| Model | Accu-Rate |
| Flow Rate | See Chart |



SHIPPING DIMENSIONS

| | |
|-----------------|--------------|
| Width | 55" (1.39 m) |
| Length | 56" (1.42 m) |
| Height | 60" (1.52 m) |
| Weight Estimate | TBD |

CERTIFICATION

| | |
|-------|---|
| Drive | Class 1, Group D – Class II, Groups F & G |
| Pump | CSA |

| Pressure (PSI) | L/Hr w/ Std. 12" Pulley |
|----------------|-------------------------|
| 100 | 31.2 |
| 200 | 29.2 |
| 300 | 27 |
| 400 | 26.4 |
| 500 | 25 |
| 600 | 24.8 |
| 700 | 24.5 |
| 800 | 24 |
| 900 | 23.4 |
| 1000 | 23 |
| 1500 | 22.8 |
| 2000 | 21.6 |
| 2500 | 21 |
| 3000 | 20.6 |