

**LINE HEATER**

**UNIT: LH01**

**PERFORMANCE**

BTU Rating	2 MM BTU/HR
Primary Coil Pressure Rating	2015 PSI (13892 kPa)
Primary Coil Piping Size	3" (88.9 mm)
Primary Coil Length	85' – 9 1/2" (26.15 m)
Secondary Coil Pressure Rating	1346 PSI (9280 kPa)
Secondary Coil Piping Size	3" (88.9 mm)
Secondary Coil Length	201' – 11" (61.54 m)
Bath Volume	72.5 bbl (11.54 m3)
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-20°F (-29°C)

**COIL SPECIFICATIONS**

Radiography	100%
Post Weld Heat Treatment	Yes
Corrosion Allowance	0.125" (3.2 mm)

**BURNER SPECIFICATIONS**

Burner Fuel	Natural Gas
Burner Management System	Profire
Model	2100
Voltage	24 VDC

**CHOKE & MANIFOLD**

Choke Make	None
Choke Model	None
Choke Size	3" (88.9 mm)

**SHIPPING DIMENSIONS**

Width	8' – 6" (2.6 m)
Length	32' – 2" (9.8 m)
Height	10' – 9" (3.27 m)
Dry Weight Estimate	TBD

**CERTIFICATION**

Coil Piping	ASME B31.3
Province(s) of Registration	AB, BC, SK
Sour Service	Yes

