

**LINE HEATER**

**UNIT: LH022**

**PERFORMANCE**

BTU Rating	2.0 MM BTU/HR
Primary Coil Pressure Rating	5000 PSI (34 MPa)
Primary Coil Piping Size	3" (76.2 mm)
Primary Coil Length	165' (50.3 m)
Secondary Coil Pressure Rating	5000 PSI (34 MPa)
Secondary Coil Piping Size	3" (76.2 mm)
Secondary Coil Length	165' (50.3 m)
Bath Volume	TBD
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-50°F (-45°C)

**COIL SPECIFICATIONS**

Radiography	100%
Post Weld Heat Treatment	Yes
Corrosion Allowance	0.125" (3.2 mm)

**BURNER SPECIFICATIONS**

Burner Fuel	Propane/Natural Gas
Burner Management System	Profire
Model	2100
Voltage	24 VDC

**CHOKE & MANIFOLD**

Choke Make	TBD
Choke Model	TBD
Choke Size	3" (88.9 mm)

**SHIPPING DIMENSIONS**

Width	9' (2.74 m)
Length	31' (12.75 m)
Height	11'-5" (3.5 m)
Dry Weight Estimate	28,100 lbs (12,746 kg)

**CERTIFICATION**

Coil Piping	ASME B31.3
Province(s) of Registration	AB, BC, SK, MB
Sour Service	Yes

