

LINE HEATER

UNIT: LH202

PERFORMANCE

BTU Rating Input	Propane-3 MMBTU/hr, NG 1.7 MMBTU/hr
Minimum/Maximum Rated Operating Temperature of Vessel	-20°F/200°F (-29°C/93°C)
Primary Coil Size	4 in (101.6 mm)
Primary Coil Length	O/A 275 ft. (78.33 m)
Primary Coil Pressure Rating	5,000 psig (34.47 MPag)
Secondary Coil Size	4 in (101.6 mm)
Secondary Coil Length	O/A 275 ft. (78.33 m)
Secondary Coil Pressure Rating	5,000 psig (34.47 MPag)

BURNER

Burner Fuel Type	Propane or Natural Gas
Burner System	Kenilworth
Burner Type	Profire 2100
Ignition Type	Natco (modified)

CHOKE & MANIFOLD

Choke Type	N/A
Choke Size	4-1/16 in
Valve	Cameron-Gate
Valve Size	4-1/16 in

SHIPPING DIMENSIONS

Width	9 ft (2.74 m)
Length	40.5 ft (12.75 m)
Height	12 ft 9 in (3.93 m)
Weight Estimate	49,280 lbs (22,400 kgs)

CERTIFICATION

Vessel	N/A
Piping	ASME B31.3
Province(s) of Registration	AB
Sour Service NACE Standard	MR0175

