

**LINE HEATER**

**UNIT: LH212**

**PERFORMANCE**

BTU Rating Input	1.5 MM BTU/HR
Primary Coil Size	3 in (76.2 mm)
Primary Coil Length	140 ft. 9 in. (42.9 m)
Primary Coil Pressure Rating	5,625 psig (39 MPag)
Secondary Coil Size	3 in (76.2 mm)
Secondary Coil Length	83 ft. 11 in. (25.6 m)
Secondary Coil Pressure Rating	2,395 psig (17 MPag)
Bath Volume (approximate)	37.7 bbl (6 m <sup>3</sup> )
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-20°F (-29°C)

**BURNER**

Burner Fuel Type	Propane or Natural Gas
Burner System	Kenilworth Profire
Burner Type	Profire 2100
Ignition Type	Natco (modified)

**CHOKE & MANIFOLD**

Choke Type	TBD
Choke Size	TBD
Valve	TBD

**SHIPPING DIMENSIONS**

Width	8' (2.44 m)
Length	28' (8.53 m)
Height	10' – 2" (3.10 m)
Weight Estimate	17,500 lbs (7,937 kg)

**CERTIFICATION**

Piping	ASME B31.3
Province(s) of Registration	AB
Sour Service NACE Standard	MR0175

