

ELECTRICAL DISTRIBUTION CENTER

UNIT: EDC02

PERFORMANCE

Base Rating	200 kW
Mount	Skid

MAIN FUSED DISCONNECT

Voltage	480 Volts
Amperage	400 Amps

SPLITTER

Voltage	480 Volts
Phases	3 Phase
Amperage	400 Amps

TRANSFORMER FUSED DISCONNECT

Voltage	480 Volts
Phases	3 Phase
Amperage	50 Amps

VARIABLE FREQUENCY DRIVE DISCONNECT

Phases	3 Phase
Amperage	550 Amps

TRANSFORMER

Voltage	480 V AC – 120/208 V AC
Phases	3 Phase
Wire	4

DISTRIBUTION PANEL

Voltage	120/208 Volts
Phases	3 Phase
Amperage	200 Amps

MOTOR STARTER(S)

Quantity	2
Voltage	2 @ 120 Volts
Phases	2 @ Single
Amperage	2 @ 40 Amps
Rated Horse Power	2 @ 1 HP



VARIABLE FREQUENCY DRIVE

Voltage	480 Volts
Rated Horse Power	100 HP

SHIPPING DIMENSIONS

Width	6' (1.83 m)
Length	12' (3.66 m)
Height	10' (3.05 m)
Weight Estimate	Approx. 4000lbs. (1815 kg)

CERTIFICATION

Package	CSA
Area Classification	General Purpose

