

FLARE KNOCK OUT DRUM

UNIT: FKO09

PERFORMANCE

| | |
|------------------------------------|-----------------------|
| Maximum Allowable Working Pressure | 14.7 psi (101 kPa) |
| Maximum Operating Temperature | 100°F (38°C) |
| Minimum Operating Temperature | -20°F (-29°C) |
| Storage Capacity | 677 Liters (4.25 bbl) |

DRUM

| | |
|-------------------|--------------------------|
| Vessel Diameter | 30" (762 mm) |
| Vessel Length S/S | 60" (1524 mm) |
| Inlet | 3" (88.9 mm) CL150 |
| Outlet | 3" (88.9 mm) CL150 |
| Drain | 2" (60.3 mm) 3M Coupling |
| Load Out | 2" (60.3 mm) 3M Coupling |
| Clean Out | 8" (219.1 mm) CL150 |
| Auxiliary | 2" (60.3 mm) 3M Coupling |
| Auxiliary | 3" (88.9 mm) CL150 |

EQUIPMENT

| | |
|-------------|-------------|
| Level Gauge | Sight Glass |
|-------------|-------------|

SHIPPING DIMENSIONS

| | |
|-----------------|--------------------|
| Width | 2'-6" (0.762 m) |
| Length | 6'-8" (2.03m) |
| Height | 3'-9" (1.14 m) |
| Weight Estimate | 1250 lbs. (567 kg) |

CERTIFICATION

| | |
|-----------------------------|-----|
| Vessel | N/A |
| Piping | N/A |
| Province(s) of Registration | N/A |
| Service | N/A |

