

LINE HEATER
UNIT: LH010
PERFORMANCE

BTU Rating	1.5 MM BTU/HR
Primary Coil Pressure Rating	5000 PSI (34 MPa)
Primary Coil Piping Size	3" (76.2 mm)
Primary Coil Length	254'-10 3/4" (77.7 m)
Secondary Coil Pressure Rating	2500 PSI (17 MPa)
Secondary Coil Piping Size	3" (76.2 mm)
Secondary Coil Length	254'-10 3/4" (77.7 m)
Bath Volume	81.7 bbl (13 m3)
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-20°F (-29°C)

COIL SPECIFICATIONS

Radiography	100%
Post Weld Heat Treatment	Yes
Corrosion Allowance	0.125" (3.2 mm)

BURNER SPECIFICATIONS

Burner Fuel	Propane/Natural Gas
Burner Management System	Profire
Model	2100
Voltage	24 VDC


CHOKE & MANIFOLD

Choke Make	TBD
Choke Model	TBD
Choke Size	3" (88.9 mm)

SHIPPING DIMENSIONS

Width	8' (2.43 m)
Length	37' (11.28 m)
Height	8'-7" (2.65 m)
Dry Weight Estimate	40,000 lb (18,143 kg)

CERTIFICATION

Coil Piping	ASME B31.3
Province(s) of Registration	AB
Sour Service	Yes

