



LINE HEATER UNIT: LH023

PERFORMANCE

BTU Rating	1.5 MM BTU/HR
Primary Coil Pressure Rating	5000 PSI (34 MPa)
Primary Coil Piping Size	3" (76.2 mm)
Primary Coil Length	136' (41.45 m)
Secondary Coil Pressure Rating	5000 PSI (34 MPa)
Secondary Coil Piping Size	3" (76.2 mm)
Secondary Coil Length	136' (41.45 m)
Bath Volume	40.25 bbl (6.4 m ³)
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-20°F (-29°C)

COIL SPECIFICATIONS

Radiography	100%
Post Weld Heat Treatment	Yes
Corrosion Allowance	0.125" (3.2 mm)



Burner Fuel	Propane/Natural Gas
Burner Management System	Profire
Model	2100
Voltage	24 VDC



CHOKE & MANIFOLD

Choke Make	TBD
Choke Model	TBD
Choke Size	3" (88.9 mm)

SHIPPING DIMENSIONS

Width	6'-7" (2.04 m)
Length	29'-9" (9.1 m)
Height	10' (3.04 m)
Dry Weight Estimate	25,000 lb (11,339.8 kg)

CERTIFICATION

Coil Piping	ASME B31.3
Province(s) of Registration	AB
Sour Service	Yes

