

LINE HEATER
UNIT: LH038
PERFORMANCE

BTU Rating Input	2 MMBTU/hr
Primary Coil Size	4" (101.6 mm)
Primary Coil Length	160' (48.76 m)
Primary Coil Pressure Rating	10,000 psi (68.952 MPa)
Secondary Coil Size	N/A
Secondary Coil Length	N/A
Secondary Coil Pressure Rating	N/A
Bath Volume	132 bbl (21 m ³)
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-40°F (-40°C)

COIL SPECIFICATIONS

Radiography	100%
Post Weld Heat Treatment	Yes
Corrosion Allowance	0.125" (3.2 mm)

BURNER

Burner Fuel Type	Propane
Burner Management System	Profire
Model	2100
Voltage	24 VDC

CHOKE & MANIFOLD

Choke Type	N/A
Choke Size	N/A
Valve	N/A
Valve Size	N/A

SHIPPING DIMENSIONS

Width	8' 6" (2.59 m)
Length	33' 6" (10.21 m)
Height	9' 2" (2.79 m)
Weight Estimate	43,000 lbs. (19,504 kg)

CERTIFICATION

Piping	ASME B31.3
Province(s) of Registration	AB
Sour Service NACE Standard	MR0175

