

**LINE HEATER**
**UNIT: LH103**
**PERFORMANCE**

BTU Rating Input	1.5 MMBTU/hr
Primary Coil Size	3 in (76.2 mm)
Primary Coil Length	O/A 257 ft. (78 m)
Primary Coil Pressure Rating	3,500 psig (24 MPag)
Secondary Coil Size	N/A
Secondary Coil Length	N/A
Secondary Coil Pressure Rating	N/A
Bath Volume	28.3 bbl (4.5 m <sup>3</sup> )
Maximum Rated Operating Temperature of Vessel	200°F (93°C)
Minimum Rated Operating Temperature of Vessel	-20°F (-29°C)

**BURNER**

Burner Fuel Type	Propane or Natural Gas
Burner System	Kenilworth Profile
Burner Type	Profire 2100
Ignition Type	Natco (modified)


**CHOKE & MANIFOLD/AUXILLIARY EQUIPMENT**

Choke Make	N/A
Choke Model	N/A
Choke Size	N/A
2 Bath Fluid Transfer Pump	5 hp

**SHIPPING DIMENSIONS**

Width	8'-10" ft (2.69 m)
Length	26'-7" ft (8.1 m)
Height	9'-8" ft (2.94 m)
Weight Estimate	10,802 lbs (4,910 kgs)

**CERTIFICATION**

Vessel	N/A
Piping	ASME B31.3
Province(s) of Registration	AB
Sour Service NACE Standard	MR0175

