

LINE HEATER
UNIT: LH11
PERFORMANCE

BTU Rating	2MM BTU/HR
Primary Coil Pressure Rating	5020 PSI (34.6 MPa)
Primary Coil Piping Size	3" (76.2 mm)
Primary Coil Length	183'-8" (56.0 m)
Secondary Coil Pressure Rating	5020 PSI (34.6 MPa)
Secondary Coil Piping Size	3" (76.2 mm)
Secondary Coil Length	183'-8" (56.0 m)
Bath Volume	61.9 bbl (9.8 m3)
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-50°F (-45°C)

COIL SPECIFICATIONS

Radiography	100%
Magnetic Particle	None
Post Weld Heat Treatment	Yes
Corrosion Allowance	0.125" (3.00 mm)

BURNER SPECIFICATIONS

Burner Fuel	Natural Gas
Burner Management System	ProFire
Model	2100
Voltage	24 V DC


CHOKE & MANIFOLD

Choke Make	None
Choke Model	None
Choke Size	3" CL2500 RTJ

SHIPPING DIMENSIONS

Width	8' (2.44 m)
Length	31'-10.5" (9.57 m)
Height	10'- ½ " (3.06 m)
Dry Weight Estimate	24,500 lbs (11,113 kg)


CERTIFICATION

Coil Piping	ASME B31.3
Province(s) of Registration	AB, BC, SK
Sour Service	YES
Burner Management System	CSA B149.3