

LINE HEATER

UNIT: LH12

PERFORMANCE

BTU Rating	2MM BTU/HR
Primary Coil Pressure Rating	4500 PSI (31.0 MPa)
Primary Coil Piping Size	4" (101.6 mm)
Primary Coil Length	256'-5" (78.1 m)
Secondary Coil Pressure Rating	4500 PSI (31.0 MPa)
Secondary Coil Piping Size	4" (101.6 mm)
Secondary Coil Length	256'-5" (78.1 m)
Bath Volume	49 bbl (7.82 m3)
Maximum Rated Operating Temperature	200°F (93°C)
Minimum Rated Operating Temperature	-50°F (-45°C)

BURNER SPECIFICATIONS

Burner Fuel	Fuel Gas
Burner Management System	ProFire
Model	2100
Voltage	24 V DC

CHOKE & MANIFOLD

Choke Make	None
Choke Model	None
Choke Size	4" CL2500 RTJ

SHIPPING DIMENSIONS

Width	7'-6" (2.31 m)
Length	31'-4 7/8" (9.58 m)
Height	10'-1/2" (3.06 m)
Weight Estimate	24,500 LBS (11,113 kg)

CERTIFICATION

Coil Piping	ASME B31.3
Province(s) of Registration	AB, BC
Sour Service	YES
Burner Management System	CSA B149.3

