

FLOWLINE RESTRAINT SYSTEMS

PERFORMANCE

Maximum High Pressure Rating		
	2" (50.8 mm)	20,000 psi (137.9 MPa)
	3" (76.2 mm)	15,000 psi (103.42)
	4" (101.6 mm)	10,000 psi (68.95 MPa)
Minimum/Maximum Rated Operating Temperature		-22°F/212°F (-30°C/100°C)
FRS Ribs (Red)		4' (1.21 m)
FRS Spines (Blue)		4' (1.21 m) to 20' (6.09 m)
Maximum Low Pressure Rating		
	2" (50.8 mm)	5,000 psi (34.47 MPa)
	3" (76.2 mm)	2,000 psi (13.79 MPa)
	4" (101.6 mm)	2,000 psi (13.79 MPa)
Minimum/Maximum Rated Operating Temperature		-40°F/94°F (-40°C/90°C)
FRS Ribs (Yellow)		10' (3 m)
FRS Spines (Yellow)		20' (6.09 m)

CONTAINER DIMENSIONS

Width	7' 2" (2.19 m)
Height	9' 2" (2.79 m)
Length	11' 8" (3.56 m)
Weight Estimate	6,000 lbs. (2,721 kg)

TRAILER DIMENSIONS

Width	7' 6" (2.28 m)
Length	8" (2.44 m)
Height	12' (3.65 m)
Weight Estimate	7,000 lbs. (3,175 kg)



CERTIFICATION

Anchors receive Thickness Ultrasonic Testing annually.

Slings visually inspected prior to each use, removed from service and destroyed if damaged.

Manufactured of corrosion resistant materials.

